

Model 2100CCD 6 Sensor CCD



Standard Hardware

- Convenient rolling cabinet with integrated storage
- 17" Monitor
- Color Printer
- Network card and modem
- Soundcard and speakers
- 3-year electronic parts warranty
- Premium Dell computer platform
- Infrared mouse
- Console keyboard
- All new sensors
- Wheel sensor keypad controls
- Wheel clamps with 22" range, non-centering
- Steering wheel lock
- Brake pedal depressor

Features

- Total 4-Wheel alignment
- Front and rear camber
- Front caster
- Front and rear toe
- Thrust angles
- SAI and included angle
- Front set back

Alignment Procedures

- Pro 32 Wizards
- Elevated adjustments
- Rear shim program
- Multiple A-arm adjust
- On demand help
- Vehicle adjustment videos
- Bushing calculator

Set Up

- Mfg. specifications - 30 years
- Customer data entry
- Multiple languages

Optional

- Lift wiring kit
- Remote display kit
- Sensor calibration fixture
- Wheel clamp extension - 28" range
- Stainless steel turntables

Equipment Specifications

- Wheel size 10" - 22"
- Tire diameter to 38"
- Tread width 48" - 96"
- Wheel base 48" - 200"

Model 2310CCD Corded & 2310CCDW Wireless 8 Sensor CCD



Standard Hardware

- Convenient rolling cabinet with integrated storage
- 19" Monitor
- Color Printer
- Network card and modem
- Soundcard and speakers
- 3-year electronic parts warranty
- Premium Dell computer platform
- Platinum software program with enhanced OEM Wizard Program
- Infrared mouse
- Console keyboard
- All new sensors
- Wheel sensor keypad controls
- Wheel clamps with 22" range, non-centering
- Handheld remote control
- Steering wheel lock
- Brake pedal depressor

Alignment Procedures

- Pro 32 Wizards
- Elevated adjustments
- Rear shim programs
- Drag link adjustments
- Steering axis inclination
- Multiple A-arm adjust
- Front Bushing Program
- EZ tow
- Cradle adjust
- On demand help
- Vehicle adjustment videos
- Drive complaint diagnostics
- Vehicle dimensions
- Cross value visibility

Set Up

- Mfg. specifications - 30 years
- Customer database storage
- Programmable alignment procedure steps
- Multiple language unit

Optional

- Lift wiring kit
- Remote display kit
- Voice activated alignment kit
- Sensor calibration fixture
- Wireless upgrade kit
- Wheel clamp extension - 28" range
- Stainless steel turntables
- 19" LCD Monitor

Equipment Specifications

- Wheel size 10" - 22"
- Tire diameter to 38"
- Tread width 48" - 96"
- Wheel base 48" - 200"