

# 5602HP & 5602



Convenient storage bins with built-in inflation gauge, hose and bleeder valve.

Tilt tower with pneumatic locks & mount/demount head retractor



Pneumatic mounting helper provides:

- Hands-free - Easy mounting of the most difficult high performance low profile tires.
- Integrated top roller - Easily rolls top bead down, bead depressor holds the bead in the drop center, preventing accidental reseating.
- No scratching - Tire changer never touches rims, removing any danger of accidental damage.
- Simple operation - 15 minutes average training time.



Model 5602HP Shown\*



Extra wide base eliminates turntable interference while bead breaking, as well as creating a convenient pedal location. Two position bead breaker.



- Non-opposing 3-position adjustable jaws. Outside clamps up to 25" with integrated plastic protection to eliminate wheel damage.
- Inflation jets built into the clamps ensure maximum pressure where you need it, when you need it.

## Specifications:

Tire Diameter	40"	1016 cm
Rim/Tire Assembly Width	15"	375 cm
Rim Width	15"	375 cm
Turntable/Outside Clamping	10-25"	254-635 mm
Turntable/Inside Clamping	12-28"	305-711 mm
Bead Breaking Power	5600 lbs.	2541 kg
Air Pressure Requirement	110-170 psi	7.5-11.7 bar
Motor	1 HP	
Electrical Requirement	120 vac; 20 A; 60 hz	
Weight	710 lbs.	322 kg
Overall Dimensions: Width	43"	1092 mm
Depth	52"	1321 mm
Height	75"	1905 mm